



Customer Number 22,852
Attorney Docket No. 02481.1839

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application of: Robert Frederick VEASEY et al.)
Application No.: 10/790,225) Group Art Unit: 3763
Filed: March 2, 2004) Examiner: Not yet available
For: IMPROVEMENTS IN AND RELATING TO A PEN-)
TYPE INJECTOR)

MAIL STOP MISSING PART
Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

CLAIM FOR PRIORITY

Under the provisions of Section 119 of 35 U.S.C., applicants hereby claim the benefit of the filing date of Great Britain Application No. 03 04822.0, filed March 3, 2003, for the above identified United States Patent Application.

In support of applicants' claim for priority, filed herewith is one certified copy of the above.

Respectfully submitted,

FINNEGAN, HENDERSON, FARABOW,
GARRETT & DUNNER, L.L.P.

Dated: August 20, 2004
Enclosure
EFC/FPD/blc

By: 
Ernest F. Chapman
Reg. No. 25,961



THIS PAGE BLANK (USPTO)



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

Also certify that the attached copy of the request for grant of a Patent (Form 1/77) bears an amendment, effected by this office, following a request by the applicant and agreed to by the Comptroller-General.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name in which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., p.l.c. or PLC.

Registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Andrew Gensey


Dated 18 May 2004

**CERTIFIED COPY OF
PRIORITY DOCUMENT**

THIS PAGE BLANK (USPTO)

Patents Form 1/77

Patents 1977
(Rule 16)



1/77

Request for grant of a patent

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1.	Your reference	JAM/P96042UK		
2.	Patent application number (The Patent Office will fill in this part)	03 MAR 2003	04MAR03 E789261-1 000351 P01/7700 0.00-0304822.0	
3.	Full name, address and postcode of the or of each applicant (underline all surnames)	DCA International Limited 19 Church Street Warwick CV34 4AB		
	Patents ADP number (if you know it)	0304822.0		
	If the applicant is a corporate body, give the country/state of its incorporation	8578064001		
4.	Title of the invention	Improvements in and relating to a pen-type injector		
5.	Name of your agent (if you have one)	Marks & Clerk 49 Stoney Street NOTTINGHAM NG1 1LX ADP No. 00000018015		
	"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)	2-5-9-03		
	Patents ADP number (if you know it)			
6.	If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or each of these earlier applications and (if you know it) the or each application number	Country	Priority application number (if you know it)	Date of filing (day / month / year)
7.	If this application is divided or otherwise derived from an earlier UK application, give the number and filing date of the earlier application	Number of earlier application	Date of filing (day / month / year)	
8.	Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'yes' if: a) any applicant named in part 3 is not an inventor, or b) there is an inventor who is not named as an applicant, or c) any named applicant is a corporate body.			

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document

Continuation sheets of this form

Description 11

Claim(s) 3

Abstract -

Drawing(s) 7 X

10. If you are also filing any of the following, state how many against each item.

Priority documents

Translation of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patents Form 9/77) ✓

Request for substantive examination (Patents Form 10/77)

Any other documents (please specify)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date

3 March 2003

John A Moffat

12. Name and daytime telephone number of person to contact in the United Kingdom

J A Moffat
(024) 7622 2756/7145

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Improvements in and relating to a pen-type injector

The present invention relates to pen-type injectors, that is to injectors of the kind that provide for administration by injection of medicinal products from a multidose cartridge. In particular, the present invention relates to such injectors where a user may set the dose.

Such injectors have application where regular injection by persons without formal medical training occurs. This is increasingly common amongst those having diabetes where self-treatment enables such persons to conduct effective management of their diabetes.

These circumstances set a number of requirements for pen-type injectors of this kind. The injector must be robust in construction, yet easy to use both in terms of the manipulation of the parts and understanding by a user of its operation. In the case of those with diabetes, many users will be physically infirm and may also have impaired vision. Where the injector is to be disposable rather than reusable, the injector should be cheap to manufacture and easy to dispose of (preferably being suitable for recycling).

It is an advantage of the present invention that an improved pen-type injector is provided.

According to a first aspect of the present invention, a pen-type injector comprises a housing;
a piston rod adapted to operate through the housing;
a dose dial sleeve located between the housing and the piston rod, the dose dial sleeve having a helical thread of first lead;
a drive sleeve located between the dose dial sleeve and the piston rod, the drive sleeve having a helical groove of second lead;
characterised in that the first lead of the helical thread and the second lead of the helical groove are the same.

Preferably, the piston rod has a first threaded portion at a first end and a second threaded portion at a second end;

an insert or radially inwardly extending flange is located in the housing and

5 through which the first threaded portion of the piston rod may rotate;

the dose dial sleeve being rotatable with respect to the housing and the insert;

the drive sleeve being releasably connected to the dose dial sleeve and

connected to the piston rod for rotation with respect thereto along the second threaded portion of the piston rod;

10 a button is located on the dose dial sleeve and rotatable with respect to the dose dial sleeve; and

clutch means are provided which upon depression of the button permit rotation between the dose dial sleeve and the drive sleeve.

15 Preferably, the injector further comprises a nut which is rotatable with respect to the drive sleeve and axially displaceable but not rotatable with respect to the housing.

20 More preferably, the drive sleeve is provided at a first end with first and second flanges with an intermediate thread between the first and second flanges, the nut being disposed between the first and second flanges and keyed to the housing by spline means. Additionally, a first radial stop may be provided on a second face of the nut and a second radial stop may be provided on a first face of the second flange.

25

Preferably, the first thread of the piston rod is oppositely disposed to the second thread of the piston rod.

30 Preferably, a second end of the clutch is provided with a plurality of dog teeth adapted to engage with a second end of the dose dial sleeve.

Preferably, the pen-type injector further includes clicker means disposed between the clutch means and spline means provided on the housing.

More preferably, the clicker means comprises a sleeve provided at a first end with a helically extending arm, a free end of the arm having a toothed member, and at a second end with a plurality of circumferentially directed saw teeth adapted to engage a corresponding plurality of circumferentially saw teeth provided on the clutch means.

Alternatively, the clicker means comprises a sleeve provided at a first end with at least one helically extending arm and at least one spring member, a free end of the arm having a toothed member, and at a second end with a plurality of circumferentially directed saw teeth adapted to engage a corresponding plurality of circumferentially directed saw teeth provided on the clutch means.

15

Preferably, the main housing is provided with a plurality of maximum dose stops adapted to be abutted by a radial stop provided on the dose dial sleeve. More preferably, at least one of the maximum dose stops comprises a radial stop located between a helical rib and spline means provided at a second end of the housing. Alternatively, at least one of the maximum dose stops comprises a part of a raised window portion provided at a second end of the housing.

20

Preferably, the dose dial sleeve is provided with a plurality of radially extending members adapted to abut a corresponding plurality of radial stops provided at a second end of the housing.

25

The invention will now be described with reference to the accompanying drawings, in which:-

Figure 1 shows a sectional view of a pen-type injector in accordance with the present invention in a first, cartridge full, position;

30

Figure 2 shows a sectional view of the pen-type injector of Figure 1 in a second, maximum first dose dialed, position;

Figure 3 shows a sectional view of the pen-type injector of Figure 1 in a third, first maximum first dose dispensed, position;

Figure 4 shows a sectional view of the pen-type injector of Figure 1 in a fourth, final dose dialed, position;

- 5 Figure 5 shows a sectional view of the pen-type injector of Figure 1 in a fifth, final dose dispensed, position;

Figure 6 shows a cut-away view of a first detail of the pen-type injector of Figure 1;

- 10 Figure 7 shows a partially cut-away view of a second detail of the pen-type injector of Figure 1;

Figure 8 shows a partially cut-away view of a third detail of the pen-type injector of Figure 1;

Figure 9 shows the relative movement of parts of the pen-type injector shown in Figure 1 during dialing up of a dose;

- 15 Figure 10 shows the relative movement of parts of the pen-type injector shown in Figure 1 during dialing down of a dose;

Figure 11 shows the relative movement of parts of the pen-type injector shown in Figure 1 during dispensing of a dose;

- 20 Figure 12 shows a partially cut-away view of the pen-type injector of Figure 1 in the second, maximum first dose dialed, position;

Figure 13 shows a partially cut-away view of the pen-type injector of Figure 1 in the fourth, final dose dialed, position;

Figure 14 shows a partially cut-away view of the pen-type injector of Figure 1 in one of the first, third or fifth positions;

- 25 Figure 15 shows a cut-away view of a first part of a main housing of the pen-type injector of Figure 1; and

Figure 16 shows a cut-away view of a second part of the main housing of the pen-type injector of Figure 1.

- 30 Referring first to Figures 1 to 5, there may be seen a pen-type injector in accordance with the present invention in a number of positions.

The pen-type injector comprises a housing having a first cartridge retaining part 2, and second main housing part 4. A first end of the cartridge retaining means 2 and a second end of the main housing 4 are secured together by retaining features 6. In the illustrated embodiment, the cartridge retaining means 2 is secured within the second end of the main housing 4.

A cartridge 8 from which a number of doses of medicinal product may be dispensed is provided in the cartridge retaining part 2. A piston 10 is retained in a first end of the cartridge 8.

A removable cap 12 is releasably retained over a second end of the cartridge retaining part 2. In use the removable cap 12 can be replaced by a user with a suitable needle unit (not shown). A replaceable cap 14 is used to cover the cartridge retaining part 2 extending from the main housing 4. Preferably, the outer dimensions of the replaceable cap 14 are similar or identical to the outer dimensions of the main housing 4 to provide the impression of a unitary whole when the replaceable cap 14 is in position covering the cartridge retaining part 2.

In the illustrated embodiment, an insert 16 is provided at a first end of the main housing 4. The insert 16 is secured against rotational or longitudinal motion. The insert 16 is provided with a threaded circular opening 18 extending therethrough. Alternatively, the insert may be formed integrally with the main housing 4 the form of a radially inwardly directed flange having an internal thread.

A first thread 19 extends from a first end of a piston rod 20. The piston rod 20 is of generally circular section. The first end of the piston rod 20 extends through the threaded opening 18 in the insert 16. A pressure foot 22 is located at the first end of the piston rod 20. The pressure foot 22 is disposed to abut a second end of the cartridge piston 10. A second thread 24 extends from a second end of the piston rod 20. In the illustrated embodiment the second thread 24 comprises a series of part threads rather than a complete thread. The illustrated embodiment

is easier to manufacture and helps reduce the overall force required for a user to cause medicinal product to be dispensed.

5 The first thread 19 and the second thread 24 are oppositely disposed. The second end of the piston rod 20 is provided with a receiving recess 26.

10 A drive sleeve 30 extends about the piston rod 20. The drive sleeve 30 is generally cylindrical. The drive sleeve 30 is provided at a first end with a first radially extending flange 32. A second radially extending flange 34 is provided spaced a distance along the drive sleeve 30 from the first flange 32. An intermediate thread 36 is provided on an outer part of the drive sleeve 30 extending between the first flange 32 and the second flange 34. A helical groove 38 extends along the internal surface of the drive sleeve 30. The second thread 24 of the piston rod 20 is adapted to work within the helical groove 38.

15 A first end of the first flange 32 is adapted to conform to a second side of the insert 16.

20 A nut 40 is located between the drive sleeve 30 and the main housing 2, disposed between the first flange 32 and the second flange 34. In the illustrated embodiment the nut 40 is a half-nut. This assists in the assembly of the injector. The nut 40 has an internal thread matching the intermediate thread 36. The outer surface of the nut 40 and an internal surface of the main housing 4 are keyed together by splines 42 (see Figures 10, 11, 15 and 16) to prevent relative rotation between the nut 40 and the main housing 4, while allowing relative longitudinal movement therebetween.

30 A shoulder 37 is formed between a second end of the drive sleeve 30 and an extension 38 provided at the second end of the drive sleeve 30. The extension 38 has reduced inner and outer diameters in comparison to the remainder of the drive sleeve 30. A second end of the extension 38 is provided with a radially outwardly directed flange 39.

A clicker 50 and a clutch 60 are disposed about the drive sleeve 30, between the drive sleeve 30 and a dose dial sleeve 70 (to be described below).

- 5 The clicker 50 is located adjacent the second flange 34 of the drive sleeve 30. The clicker 50 is generally cylindrical and is provided at a first end with a flexible helically extending arm 52 (shown most clearly in Figure 6). A free end of the arm 52 is provided with a radially directed toothed member 54. A second end of the clicker 50 is provided with a series of circumferentially directed saw teeth 56
10 (cf Figure 7). Each saw tooth comprises a longitudinally directed surface and an inclined surface.

- In an alternative embodiment (not shown) the clicker means further includes at least one spring member. The at least one spring member assists in the
15 resetting of the clutch means 60 following dispense.

- The clutch means 60 is located adjacent the second end of the drive sleeve 30. The clutch means 60 is generally cylindrical and is provided at a first end with a series of circumferentially directed saw teeth 66 (see Figure 7). Each saw tooth
20 comprises a longitudinally directed surface and an inclined surface. Towards the second end 64 of the clutch means 60 there is located a radially inwardly directed flange 62. The flange 62 of the clutch means 60 is disposed between the shoulder 37 of the drive sleeve 30 and the radially outwardly directed flange 39 of the extension 38. The second end of the clutch means 60 is provided with a
25 plurality of dog teeth 65 (Figure 8). The clutch 60 is keyed to the drive sleeve 30 by way of splines (not shown) to prevent relative rotation between the clutch 60 and the drive sleeve 30.

- In the illustrated embodiment, the clicker 50 and the clutch 60 each extend
30 approximately half the length of the drive sleeve 30. However, it will be understood that other arrangements regarding the relative lengths of these parts are possible.

The clicker 50 and the clutch means 60 are normally engaged, that is as shown in Figure 7.

- 5 A dose dial sleeve 70 is provided outside of the clicker 50 and clutch means 60 and radially inward of the main housing 4. A helical groove 74 is provided about an outer surface of the dose dial sleeve 70.

- 10 The main housing 4 is provided with a window 44 through which a part of the outer surface of the dose dial sleeve may be seen. The main housing 4 is further provided with a helical rib 46, adapted to be seated in the helical groove 74 on the outer surface of the dose dial sleeve 70. The helical rib 46 extends for a single sweep of the inner surface of the main housing 4. A first stop 100 is provided between the splines 42 and the helical rib 46 (Figure 15). A second
15 stop 102, disposed at an angle of 180° to the first stop 100 is formed by a frame surrounding the window 44 in the main housing 4 (Figure 16).

- Conveniently, a visual indication of the dose that may be dialed, for example reference numerals (not shown), is provided on the outer surface of the dose dial
20 sleeve 70. The window 44 conveniently only allows to be viewed a visual indication of the dose currently dialed.

- A second end of the dose dial sleeve 70 is provided with an inwardly directed flange in the form of number of radially extending members 75. A dose dial
25 grip 76 is disposed about an outer surface of the second end of the dose dial sleeve 70. An outer diameter of the dose dial grip 76 preferably corresponds to the outer diameter of the main housing 4. The dose dial grip 76 is secured to the dose dial sleeve 70 to prevent relative movement therebetween. The dose dial grip 76 is provided with a central opening 78. An annular recess 80 located in the
30 second end of the dose dial grip 76 extends around the opening 78.

A button 82 of generally 'T' section is provided at a second end of the pen-type injector. A stem 84 of the button 82 may extend through the opening 78 in the dose dial grip 76, through the inner diameter of the extension 38 of the drive sleeve 30 and into the receiving recess 26 of the piston rod 20. The stem 84 is retained for limited axial movement in the drive sleeve 30 and against rotation with respect thereto. A head 85 of the button 82 is generally circular. A skirt 86 depends from a periphery of the head 85. The skirt 86 is adapted to be seated in the annular recess 80 of the dose dial grip 76.

Operation of the pen-type injector in accordance with the present invention will now be described. In Figures 9, 10 and 11 arrows A, B, C, D, E, F and G represent the respective movements of the button 82, the dose dial grip 76, the dose dial sleeve 70, the drive sleeve 30, the clutch means 60, the clicker 50 and the nut 40.

To dial a dose (Figure 9) a user rotates the dose dial grip 76 (arrow A). With the clicker 50 and clutch means 60 engaged, the drive sleeve 30, the clicker 50, the clutch means 60 and the dose dial sleeve 70 rotate with the dose dial grip 76.

Audible and tactile feedback of the dose being dialed is provided by the clicker 50 and the clutch means 60. Torque is transmitted through the saw teeth 56,66 between the clicker 50 and the clutch means 60. The flexible arm 52 deforms and drags the toothed member 54 over the splines 42 to produce a click. Preferably, the splines 42 are disposed such that each click corresponds to a unit dose.

The helical groove 74 on the dose dial sleeve 70 and the helical groove 38 in the drive sleeve 30 have the same lead. This allows the dose dial sleeve 70 (arrow C) to extend from the main housing 4 and the drive sleeve 30 (arrow D) to climb the piston rod 20 at the same rate. At the limit of travel, a radial stop 104 on the dose dial sleeve 70 engages either the first stop 100 or the second stop 102 provided on the main housing 4 to prevent further movement. Rotation

of the piston rod 20 is prevented due to the opposing directions of the overhauled and driven threads on the piston rod 20.

The nut 40, keyed to the main housing 4, is advanced along the intermediate
5 thread 36 by the rotation of the drive sleeve 30 (arrow D). When the final dose dispensed position (Figures 4, 5 and 13) is reached, a radial stop 106 formed on a second surface of the nut 40 abuts a radial stop 108 on a first surface of the second flange 34 of the drive sleeve 30, preventing both the nut 40 and the drive sleeve 30 from rotating further.

10 In an alternative embodiment (not shown) a first surface of the nut 40 is provided with a radial stop for abutment with a radial stop provided on a second surface of the first flange 32. This aids location of the nut 40 at the cartridge full position during assembly of the pen-type injector.

15 Should a user inadvertently dial beyond the desired dosage, the pen-type injector allows the dosage to be dialed down without dispense of medicinal product from the cartridge (Figure 10). The dose dial grip 76 is counter rotated. This causes the system to act in reverse. The flexible arm 52 now acts as a ratchet
20 preventing the clicker from rotating. The torque transmitted through the clutch means 60 causes the saw teeth 56,66 to ride over one another to create the clicks corresponding to dialed dose reduction. Preferably the saw teeth 56,66 are so disposed that the circumferential extent of each saw tooth corresponds to a unit dose.

25 When the desired dose has been dialed, the user may then dispense this dose by depressing the button 82 (Figure 11). This displaces the clutch means 60 axially with respect to the dose dial sleeve 70 causing the dog teeth 65 to disengage. However the clutch means 60 remains keyed in rotation to the drive sleeve 30.
30 The dose dial sleeve 70 and associated dose dial grip 76 are now free to rotate (guided by the helical rib 46 located in helical groove 74).

The axial movement deforms the flexible arm 52 of the clicker 50 to ensure the saw teeth 56,66 cannot be overhauled during dispense. This prevents the drive sleeve 30 from rotating with respect to the main housing 4 though it is still free to move axially with respect thereto. This deformation is subsequently used to urge
5 the clicker 50, and the clutch 60, back along the drive sleeve 30 to restore the connection between the clutch 60 and the dose dial sleeve 70 when pressure is removed from the button 82.

The longitudinal axial movement of the drive sleeve 30 causes the piston rod 20
10 to rotate through the opening 18 in the insert 16, thereby to advance the piston 10 in the cartridge 8. Once the dialed dose has been dispensed, the dose dial sleeve 70 is prevented from further rotation by contact of a plurality of members 110 (Figure 14) extending from the dose dial grip 76 with a
15 corresponding plurality of stops 112 formed in the main housing 4 (Figures 15 and 16). In the illustrated embodiment, the members 110 extend axially from the dose dial grip 76 and have an inclined end surface. The zero dose position is determined by the abutment of one of the axially extending edges of the members 110 with a corresponding stop 112.

CLAIMS

1 A pen-type injector comprising a housing;
a piston rod adapted to operate through the housing;
5 a dose dial sleeve located between the housing and the piston rod, the dose dial sleeve having a helical thread of first lead;
a drive sleeve located between the dose dial sleeve and the piston rod, the drive sleeve having a helical groove of second lead;
characterised in that the first lead of the helical thread and the second lead of the
10 helical groove are the same.

2 A pen-type injector according to claim 1, characterised in that the piston rod has a first threaded portion at a first end and a second threaded portion at a second end;
15 an insert or radially inwardly extending flange is located in the housing and through which the first threaded portion of the piston rod may rotate;
the dose dial sleeve being rotatable with respect to the housing and the insert;
the drive sleeve being releasably connected to the dose dial sleeve and connected to the piston rod for rotation with respect thereto along the second
20 threaded portion of the piston rod;
a button is located on the dose dial sleeve and rotatable with respect to the dose dial sleeve; and
clutch means are provided which upon depression of the button permit rotation between the dose dial sleeve and the drive sleeve.

25 3 A pen-type injector according to claim 1 or claim 2, in which the injector further comprises a nut which is rotatable with respect to the drive sleeve and axially displaceable but not rotatable with respect to the housing.

30 4 A pen-type injector according to claim 3, in which the drive sleeve is provided at a first end with first and second flanges with an intermediate thread

between the first and second flanges, the nut being disposed between the first and second flanges and keyed to the housing by spline means.

5 A pen-type injector according to claim 4, in which a first radial stop is
5 provided on a second face of the nut and a second radial stop is provided on a
first face of the second flange.

6 A pen-type injector according to any of claims 2 to 5, in which the first
thread of the piston rod is oppositely disposed to the second thread of the piston
10 rod.

7 A pen-type injector according to any of claims 2 to 6, in which a second
end of the clutch is provided with a plurality of dog teeth adapted to engage with
a second end of the dose dial sleeve.

15 8 A pen-type injector according to any of claims 2 to 7, in which the pen-type
injector further includes clicker means disposed between the clutch means and
spline means provided on the housing.

20 9 A pen-type injector according to claim 8, in which the clicker means
comprises a sleeve provided at a first end with a helically extending arm, a free
end of the arm having a toothed member, and at a second end with a plurality of
circumferentially directed saw teeth adapted to engage a corresponding plurality
of circumferentially saw teeth provided on the clutch means.

25 10 A pen-type injector according to claim 8, in which the clicker means
comprises a sleeve provided at a first end with at least one helically extending
arm and at least one spring member, a free end of the arm having a toothed
member, and at a second end with a plurality of circumferentially directed saw
30 teeth adapted to engage a corresponding plurality of circumferentially directed
saw teeth provided on the clutch means.

11 A pen-type injector according to any previous claim, in which the main housing is provided with a plurality of maximum dose stops adapted to be abutted by a radial stop provided on the dose dial sleeve.

5 12 A pen-type injector according to claim 11, in which at least one of the maximum dose stops comprises a radial stop located between a helical rib and spline means provided at a second end of the housing.

10 13 A pen-type injector according to claim 11, in which at least one of the maximum dose stops comprises a part of a raised window portion provided at a second end of the housing.

15 14 A pen-type injector according to any previous claim, in which the dose dial sleeve is provided with a plurality of radially extending members adapted to abut a corresponding plurality of radial stops provided at a second end of the housing.

15 A pen-type injector substantially as described herein with reference to and as illustrated in the accompanying Figures.




Fig 1




Fig 2

THIS PAGE BLANK (USPTO)




Fig 3




Fig 4

THIS PAGE BLANK (USPTO)




Fig 5

THIS PAGE BLANK (USPTO)

4/7




Fig 6




Fig 7




Fig 8

THIS PAGE BLANK (USPTO)




Fig 9




Fig 10




Fig 11

THIS PAGE BLANK (USPTO)

6/7




Fig 12




Fig 13




Fig 14

THIS PAGE BLANK (USPTO)

7/7




Fig 15




Fig 16

THIS PAGE BLANK (USPTO)